

## **NEAR-NET-SHAPE POLYMERIZATION PROCESS AND MATERIALS SUITABLE FOR USE THEREWITH**

### **5 CROSS REFERENCE TO RELATED APPLICATIONS**

10 This application is a continuation-in-part application of U.S. application Serial No. 511,661, filed on February 22, 2000, which is a continuation-in-part application of International patent application No. PCT/US99/22048, filed on September 22, 1999 and designating the United States, which claims the benefit of U.S. Provisional Patent Application Serial No. 60/101,285, filed on September 22, 1998; the disclosures of all of which are incorporated herein by reference in their entirety.

### **15 FIELD OF THE INVENTION**

This invention is related to the fields of polymerization and molding. More particularly, it is related to a process for the rapid in-situ near-net-shape polymerization of semi-solid-like materials to provide objects that are dimensionally stable and precise, with very little shrinkage upon curing. The invention is further related to semi-solid-like materials useful with the process.

### **20 BACKGROUND OF THE INVENTION**

25 Dimensionally precise objects/articles find numerous applications in electronics, optics, automotive, aerospace, and other high-technology industries. Examples include optically transparent objects/articles such as various precision lenses (spherical and aspherical), ophthalmic lenses (single vision, bifocal, trifocal, and progressive), contact lenses, optical data storage disk substrates, and projection optics/lens arrays. Non-transparent but dimensionally exact parts abound, such as couplers, housings, gears, and various packaging assemblies. The most straightforward fabrication method for dimensionally precise parts is the machining, grinding, and polishing of sheet stock and, in fact, this approach is still used today for some types of ophthalmic lenses. Unfortunately, this approach is limited to simple geometries and is costly due to the relatively large amounts of skilled labor required to produce a single part. More commonly, the plastics industry relies on well-known processes such as injection molding, compression molding, transfer molding, reactive injection molding (RIM), and casting for the fabrication of geometrically complex parts.

35 Injection molding, compression molding and transfer molding require the use of thermoplastic polymers. Material choices are limited to uncrosslinked polymers that can be melted

by heat and injected at high pressures. Example polymers include polymethylmethacrylate, polystyrene, ABS (acrylonitrile-butadiene-styrene) and polycarbonate. These molding processes entail high temperature and pressure; therefore, expensive molding equipment and molds are necessary. Large parts with thick cross-sections are difficult to mold, since the heat transfer rate is slow. Long cycle times make the processes uneconomical. Additionally, finite coefficients of thermal expansion can lead to part warpage upon cooling. Thus, these processes are seldom practical for large-scale manufacturing of truly dimensionally demanding parts.

Reaction injection molding requires the use of at least two highly reactive components (A + B). Urethane is one such example, where the reactive components are monomeric isocyanates and alcohols. The components are quickly and thoroughly mixed just before injection into the mold cavity. The material is then allowed to quickly set in the cavity (cured). This methodology relies on materials that are highly reactive and generally toxic. Mechanical means for thorough mixing is part of the integral process, making the production equipment costly. The fabricated parts are also not quite dimensionally exact due to shrinkage effects associated with the polymerization process. Material selection is limited by the required reaction chemistry, as well. Thus, reactive injection molding (RIM) is limited by the need for highly reactive functional groups, the intensity of mixing prior to mold fill, and complex and expensive machinery to carry out the process.

Fabrication of precision parts has been attempted by processes generally known as casting. Casting is typically a less expensive alternative to the above processes. It is also a more flexible process, in that a great number of precursor mixtures (e.g., monomers, crosslinkers, oligomers, etc.) can be formulated to achieve different final parts and performance properties. The final parts can be thermosets, formed by a polymer network that is crosslinked to prevent melt flow. Since the precursor solution has a relatively low viscosity to facilitate mold fill, the process is a low-pressure operation, reducing the necessary equipment cost. The casting process, unfortunately, is often compromised by the high shrinkage rate of the formulated precursor mixtures, yielding inexact parts with warped shapes. The high shrinkage rate is a natural consequence of using precursors that have low to moderate viscosities. If we take an ophthalmic lens as an example, the mold defining the lens-shaped cavity generally consists of a front and a back half, and an intervening gasket. The front mold half is concave, whereas the back mold half is convex. Detailed design features distinguish the utility of the resulting lens. Hence, simple vision, bifocal, trifocal, progressive, spherical, aspherical, and toroidal lenses can all be made, in principle, but if and only if the in-situ curing process can be performed with near net-shape fidelity. This is obviously a difficult task, at best, if the material used for casting exhibits a high degree of shrinkage. Casting thus requires a mold-filling step, an activation step to trigger and sustain polymerization, and a mold-opening/ensuing cleaning step to finish the part and to recycle/re-shelf

the mold halves. To date, all known casting processes begin with a polymerizable fluid that can be easily fed into the mold cavity, i.e., at moderate pressures. Care is necessary to minimize bubble creation. A carefully designed gasket is required, applied to seal off the cavity formed by the mold halves. Then a controlled curing step is imposed to convert the liquid feed into a finished, solid object.

Most curable formulations contain carbon-carbon double bonds. Such unsaturated sites are exemplified by functional groups like acrylates, methacrylates, vinyl ethers, and vinyls. Free radical or ionic polymerization mechanisms can be induced by the appropriate initiators, triggered by either UV or heat, i.e., photo- or thermally-induced polymerization. Since the reaction mixtures must fill the cavities in as short a time as possible to allow reasonable process economies, small-molecule or oligomeric mixtures are usually employed to keep viscosities low. These systems have a significant degree of shrinkage upon cure, as high as 15% for some oligomeric mixtures, and even greater than 20% for some small molecule formulations.

Additionally, the polymerization of unsaturated species is unfortunately an exothermic reaction. When such a reactive system is cured a great deal of heat is generated. The result is a spurious temperature excursion of the cast part during cure which often leads to thermal degradation of the material, discoloration, and part warpage upon cool down and removal from the mold. This problem may be reduced by improving heat transfer. Unfortunately, heat transfer can be improved only so much, due in part to the poor thermal conductivity of most polymeric systems. Overheating during cure can also be reduced by lowering the concentration of initiator species in the starting formulation, except that decreasing the initiator concentration prolongs the curing process and can lead to incomplete curing reactions and only partially polymerized final objects.

The heat generation and shrinkage accompanying polymerization must be accommodated by specially engineered curing processes, such as zone-curing techniques, in order to produce exact parts that replicate the contours of the cavity, and to slow the curing reaction so as to reduce spurious temperature rises. The need to use a gasket to prevent leakage (material escape) and minimize introduction of air bubbles dictates limited flexibility of mechanical design. It is also difficult to have the front and back mold halves positioned in such a way so as to intentionally create a non-aligned axial offset (known as de-centration). In addition, it is difficult to have the two axes rotated to create an intentional tilt (thus introducing a prismatic effect to the ensuing lens).

Finally, since most if not all of the reactive mixture exists initially in an unpolymerized state, the process must accomplish the curing of all such as-yet unreacted material precursors so that no small-molecule, volatile species remain in the finished part. This has the effect of protracting the process duration, especially if the initiator composition is kept low so as to minimize rate of heat generation. In free radical polymerization, this problem is further exacerbated by the reaction

inhibition which occurs as a result of the presence of oxygen (either dissolved in the polymerizing liquid, or present in the vapor space surrounding the mold). Nitrogen purging of both the polymerizing liquid and of the mold cavity must be employed to keep oxygen levels low so that polymerization may occur in a timely fashion. Often nitrogen purging is not able to remove all oxygen, and parts remain only partially cured, especially near the part surfaces, leading to sticky or tacky skins. Manufacturers have gone to great lengths in order to prevent oxygen from slowing the cure reaction in the near-surface region of cast parts, often employing initiators that react with oxygen diradicals, high levels of initiators (which increases the likelihood of high-temperature excursions and yellowing), or oxygen impermeable films at the surfaces of the cured parts. Insertion of such films entails opening the mold after partially curing the object, which further has the effect of complicating the process and protracting the process duration.

#### SUMMARY OF THE INVENTION:

The present invention discloses a revolutionary approach that overcomes the above described intrinsic drawbacks of commercially established processes. It is unique in that it has the promise of becoming an extremely economical process suitable for mass manufacture. It also gives parts that are dimensionally exact. Another aspect of this disclosure is the formulation of a new class of polymerizable materials that exhibit a semi-solid-like behavior during molding, very low inherent shrinkage upon curing, and highly optimized engineering properties of the final object.

More particularly, this invention is directed to a process for the rapid in-situ near-net-shape polymerization of semi-solid-like materials to provide a cured resin material characterized by one or more macromolecular networks resulting in articles of manufacture that are dimensionally stable and precise, with very little shrinkage upon cure. The process includes the steps of mixing together a dead polymer, a reactive plasticizer and an initiator to give a semi-solid polymerizable composition; shaping the semi-solid composition into a desired geometry; and exposing the polymerizable composition to a source of polymerizing energy, to give a final product with dimensional stability and high-fidelity replication of an internal mold cavity. The article so produced can optionally be transparent and/or have resistance to impact (resilient). The resulting macromolecular network is characterized as having either i) a semi-interpenetrating crosslinked polymer network of reactive plasticizer wrapped around and within an entangled dead polymer (semi-IPN); or ii) an interpenetrating crosslinked polymer network of reactive plasticizer within an entangled dead polymer, the reactive plasticizer polymer network being further crosslinked to the dead polymer; or iii) interpenetrating reactive plasticizer polymer chains, which may be linear, branched, etc., within an entangled dead polymer. In the extreme, very little to none of the dead polymer is used and only reactive oligomers or reactive macromers are used, as long as the

material can be handled as a semi-solid. Upon polymerization, this arrangement leads to an entangled polymer (linear, branched, etc.) or to a single, uniform, crosslinked polymer network.

The reactive plasticizer may react with the dead polymer chains if the polymer has crosslinkable groups. In the presence of multifunctional monomers, two polymer networks are formed that are crosslinked together. Grafting reactions by chain transfer to the dead polymers may also occur in addition to the reactive plasticizer network formation among the dead polymers. Such systems are desirable because crosslinking of the dead polymer to the network formed by the reactive plasticizer can prevent phase separation between the two polymers. If only mono-functional reactive plasticizers are used, linear polymeric chains may be formed among the dead polymer chains. This arrangement will generally not be preferred over the crosslinked network for preparing transparent parts because uncrosslinked polymers tend to phase separate over time (kinetically limited), except in rare cases of compatibility between the two or more polymeric phases. Mixtures containing only mono-functional reactive plasticizers will often react slightly with the dead polymer chains (even when no crosslinkable side groups are present on the dead polymer), desirably producing a slightly crosslinked network having sufficient stability to prevent phase separation over time periods of interest. When a non-transparent finished part is the objective, then the above limitations are relieved.

The invention further encompasses certain semi-solid-like polymerizable compositions useful with the process. The semi-solid compositions comprise a mixture of a reactive plasticizer, an initiator and, optionally, a dead polymer. The compositions may optionally include other additives well-known in the art to effect mold release, improved stability or weatherability, non-yellowing properties, and the like.

This invention permits a broad selection of reaction chemistries to achieve precision parts with the required mechanical, thermal, optical and other desired properties. It obtains precision parts that are stress-free and flawless, with little or no birefringence. Precision products can be manufactured that are very impact-resistant or that have a prismatic geometry, or have other desirable but previously difficult-to-achieve characteristics.

#### DETAILED DESCRIPTION OF THE INVENTION:

The terms "a" and "an" as used herein and in the appended claims mean "one or more".

The term "(meth)acrylate" as used herein and in the appended claims refers to both acrylate and methacrylate.

The term "dead polymer" as used herein and in the appended claims refers to a substantially fully polymerized, generally non-reactive polymer. The term "substantially fully polymerized" as used herein and in the appended claims refers to polymers that are at least 95%

polymerized and preferably at least 98% polymerized. When certain polymer chemistries are used, the dead polymer may react with a reactive plasticizer, even if the dead polymer does not have unsaturated entities within or attached to the chain. The dead polymer may be linear or branched, homopolymer or copolymer. In the case of a copolymer, the sequence distribution may be random in sequence or blocky. The block copolymers may be tapered, or may have grafted side chains. The architecture of the dead polymer may be branched, multi-chain, comb-shaped or star-shaped, either symmetrical or non-symmetrical. Di-block, tri-block or multi-block structures all fall within the scope of this invention.

The semi-solid polymerizable composition useful in the production of precision parts is prepared, in one embodiment, by mixing the dead polymer with at least one small-molecule species, which is itself polymerizable or crosslinkable. This small-molecule species is referred to herein and in the appended claims as a "reactive plasticizer". In another embodiment, the semi-solid polymerizable core composition comprises a reactive plasticizer or a mixture of reactive plasticizers, without the presence of a dead polymer. The reactive plasticizer may encompass monomers, crosslinkers, oligomeric reactants, oligomeric crosslinkers, or macromeric reactants or macromeric crosslinkers (collectively macromers). The reactive plasticizer plasticizes the dead polymer to give a composition having the desired consistency at ambient temperature or below (i.e., able to maintain a shape for easy handling over short time periods), and at the processing temperature (i.e., malleable enough to be compressed or formed into a desired shape). The said processing temperature can be chosen conveniently to be moderately above or below ambient temperature. Alternatively, it may be preferable to formulate the reactive semi-solid compositions of the present invention using only reactive plasticizers that are low molecular weight polymers or oligomers that still possess reactive groups capable of later polymerization. In this case, the reactive plasticizer should be a longer chain molecule, of from about 1 to about 1000 repeat units, and preferably between about 1 and about 100 repeat units. These reactive plasticizers (or mixture of reactive plasticizers) have a high viscosity, preferably of greater than 1000 centipoise, at the temperature at which the material is to be handled (e.g., inserted into a mold cavity) to exhibit semi-solid behavior. Such a composition still falls within the scope of this invention because in this case a lower molecular weight distribution is used to achieve the desired viscosity reduction versus plasticization of a dead polymer with a reactive plasticizer. The reactive plasticizers can be mixtures themselves, composed of mono-functional, bi-functional, tri-functional or other homogeneous or heterogeneous multi-functional entities (heterogeneous reactive plasticizers being those that possess two or more different types of reactive functionalities).

In total, the amount and composition of the reactive plasticizer in the resulting formulation are such that the formulation is semi-solid-like and can be effectively handled with no need for a

gasket in the mold. That is, the reactive plasticizer is present in concentrations sufficient to allow malleability and moldability at the desired processing temperature and pressure; however, the mixture is non-dripping and not free-flowing over short time periods at the material storage temperature and mold closure temperature, which can be conveniently chosen to be at ambient temperatures, or slightly above or below. The amount of reactive plasticizer is generally about 0.1% to about 100% by weight, preferably from about 1% to about 50%, more preferably from about 3% to about 25%.

The types and relative amounts of reactive plasticizer and dead polymer will dictate the time and temperature-dependent visco-elastic properties of the mixture. The visco-elastic properties of the chosen compositions may be wide and varied. For the practice of the invention as disclosed herewith, it is only required that the composition be highly viscous, semi-solid or solid-like for handling and/or insertion into a mold assembly at some temperature, while being semi-solid or liquid-like (i.e., deformable) at the processing temperature to which the mold assembly is heated or cooled after closure. Since virtually all known material systems become more compliant upon heating, the molding temperature will usually, but not necessarily, be equal to or higher than the handling temperature. In principle, any reactive plasticizer system (with or without dead polymer) which can be handled as a semi-solid or solid at some temperature, and which can be made to conform to a desired geometry (with or without changing the temperature and/or using force), can be used for the practice of the invention.

If the mixture consists mostly or wholly of reactive plasticizers, it may need to be cooled or partially cured in order to achieve the semi-solid-like consistency desirable for handling. Likewise, the mold-assembly temperature (the temperature at which the semi-solid composition is inserted into the mold) may desirably be below ambient temperature to prevent dripping or leaking from the mold prior to closure. Once the mold is closed, however, it may be compressed and heated to any pressure and temperature desired to induce conformation of the material to the internal mold cavity, even if such temperatures and pressures effect a free-flowing composition within the mold cavity (i.e., a composition which becomes free-flowing at the molding temperature is not precluded, and may be desirably chosen for the molding of fine-featured parts in which the molding compound must fill in small cavities, channels, and the like).

Alternatively, the dead polymer and reactive plasticizer mixture may be chosen and mixed in such proportions so as to form a composition that is glassy and rigid at ambient temperatures. Such a material will have all the benefits of ease of handling as a semi-solid composition, and will only require that the mold temperature after closure be adjusted to the softening temperature of the mixture in order to allow sufficient deformation of the material so that it may assume the desired shape (optionally in conjunction with applied pressure).

The composition most desirable for the practice of the invention will typically consist of about 3% to about 25% of a reactive plasticizer in a dead polymer. Once combined, said preferable mixture should provide a composition that is semi-solid at room temperature, such that it may be easily handled as a discrete part or object without undue stickiness or deformability. The mixture may be more easily homogenized at an elevated temperature and discharged into discrete parts which roughly approximate the desired shape of the final object, then cooled for handling or storage. When said preferable mixture or parts are placed into a mold and heated slightly above ambient temperature, or otherwise shaped or compressed while simultaneously heated, they will deform into the desired geometry without undue resistance. Such a composition is preferable in that handling and storage may occur at room temperature, while molding or shaping into the desired geometry may occur at temperatures only slightly or moderately removed from ambient. This and other benefits of the invention will be disclosed in more detail herewith.

When used without a dead polymer or with only a small amount of dead polymer, the reactive plasticizer should be a reactive oligomer or a reactive short polymer, having at least one reactive functional group. In this case, the reactive plasticizer should be a longer chain molecule, of from about 1 to about 1000 repeat units, and preferably between about 1 and about 100 repeat units. These reactive plasticizers (or mixture of reactive plasticizers) have a high viscosity, preferably of greater than 1000 centipoise, at the temperature at which the material is to be handled (e.g., inserted into a mold cavity) to exhibit semi-solid behavior. In the case of low molecular weight reactive plasticizers, the mixture may first be slightly polymerized to create the semi-solid consistency required for downstream processing as disclosed in this invention. Alternatively, the mixture may be cooled to create the semi-solid consistency.

Polymerization initiators are added to the mixture to trigger polymerization after molding. Such initiators are well-known in the art. Optionally, other additives may be added, such as mold release agents to facilitate removal of the object from the mold after curing, non-reactive conventional plasticizers or flexibilizers, pigments, dyes, organic or inorganic fibrous or particulate reinforcing or extending fillers, thixotropic agents, indicators, inhibitors or stabilizers (weathering or non-yellowing agents), UV absorbers, surfactants, flow aids, chain transfer agents, and the like. The initiator and other optional additives may be dissolved in the reactive plasticizer component prior to combining with the dead polymer to facilitate complete dissolution into and uniform mixing with the dead polymer. Alternatively, the initiator and other optional additives may be added to the mixture just prior to polymerization, which may be preferred when thermal initiators are used.

The ingredients in the semi-solid polymerizing mixture can be blended by hand or by mechanical mixing. The ingredients can preferably be warmed slightly to soften the dead polymer component. Any suitable mixing device may be used to mechanically homogenize the mixture,



such as blenders, kneaders, extruders, mills, in-line mixers, static mixers, and the like, optionally blended at temperatures above ambient temperature, or optionally blended at pressures above or below atmospheric pressure.

In one presently preferred embodiment of the invention, an optional waiting period may be allowed during which the ingredients are not mechanically agitated. The optional waiting period may take place between the time the ingredients are initially metered into a holding container and the time at which they are homogenized mechanically or manually. Alternatively, the ingredients may be metered into a mixing device, said mixing device operated for a sufficient period to dry-blend the ingredients, then an optional waiting period may ensue before further mixing takes place. The waiting period may extend for an hour to one or more days. The waiting period may be chosen empirically and without undue experimentation as the period that gives the most efficient overall mixing process in terms of energy consumption. This embodiment of the invention may be particularly beneficial when the polymerizable mixture contains a high fraction of the dead polymer ingredient, especially when the dead polymer is glassy or rigid at ambient temperatures. Utilization of a waiting period may also be particularly beneficial when the dead polymer is thermally sensitive and so cannot be processed over an extended time at temperatures above its softening point without undue degradation, or when one or more of the reactive plasticizers is particularly volatile and so cannot be easily mixed with a high-melting-temperature polymer without undue evaporative loss of the reactive plasticizer.

By "semi-solid" and "semi-solid-like" are meant that, in essence, the polymerizable composition is a rubbery, taffy-like mass at sub-ambient, ambient, or elevated temperatures. Preferably the semi-solid mass has a sufficiently high viscosity to prevent dripping at ambient temperatures and pressures or below, but is malleable and can easily deform and conform to mold surfaces if the mold cavity is slightly heated or as a result of pressure exerted by pressing the two mold halves together, or a combination of both heat and pressure. The advantage of this semi-solid composition is that it can be pre-formed into a slab, disk, ball, or sheet, for example, which may in turn pressed between mold halves to define a lens or other object without an intervening gasket. Alternatively, a glob of this composition can be applied at slightly elevated temperature on one side of a mold cavity. The other mold half is then brought into contact with the semi-solidified mass, which is squeezed into the final desired shape by the approaching mold halves. Again, there is no need for gasketing of the mold halves, as the composition will not run out of the mold due to its viscous semi-solid-like nature (except that which is squeezed out in clamping the mold shut). Furthermore, the shaped mass may be kept at a slightly elevated temperature after mold closure to anneal away the stresses (birefringence), if any, introduced by squeezing, before the

system is exposed to a source of polymerizing energy (such as UV light or temperature) to trigger network formation (curing).

With or without the annealing step, the assembly (i.e., the front mold, the rubbery precursor polymerizable composition, and the back mold) can then be exposed to UV or heat or another polymerizing energy source to complete polymerization of the reactive plasticizers in the mixture. The reactive plasticizers set up a semi-interpenetrating polymer network within an entangled dead polymer network. In some cases, the reactive plasticizer may react with groups on the dead polymer chain to form completely crosslinked networks. Optimization of engineering properties can be accomplished by the judicious quantitation of the architecture of the reactive molecules, their concentration and composition.

In case the edges of the finished parts require dimensional precision, then a precisely matched (or measured) amount of the reaction glob (mass) must be used. The front and back mold halves can be fashioned in such a way as to allow precise telescopic fit of one within the other. In one embodiment of this invention, the semi-solid material may be placed in about the center of the mold so that when the molds are compressed together, the semi-solid will flow radially outward towards the mold edges. Such a configuration allows the semi-solid material to fill in the gap between the mold while reducing or eliminating the entrainment of bubbles, air pockets, or other void defects. During mold closure, excess material (if any) can overflow the tiny annular region and be easily trimmed off after cure. If the amount of mass discharged into the mold cavity is measured very precisely, such flash can be eliminated altogether for repetitive production of identical finished objects. Alternatively, the molds may be designed so that the compressed semi-solid material only fills in part of the mold cavity, leaving the outer edges unfilled for example. In any case, the separation distance between the molds may be easily monitored so as to control the thickness of the molded part. Part thicknesses may easily range from microns to tens of centimeters with virtually no change in processing conditions or material formulations.

If the reactive plasticizers can be designed to conservatively exhibit a total shrinkage in the neighborhood of 8% when cured in their pure state, then a mixture containing less than 50% of such plasticizers in dead polymers will give only a very small (less than 4%) total shrinkage, assuming linear property additivity. This amount of total shrinkage is manageable by most curing regimens, including blanket UV exposure (for photo-cure) and rapid temperature spikes (for thermal-cure). In certain realistic cases, the intrinsic shrinkage of oligomeric reactive plasticizers may be about 5%, yet the maximum amount used in the formulation for plasticization may be only 10% by weight, giving rise to a system than shrinks approximately 0.5%. In certain other realistic cases, the intrinsic shrinkage of small molecule reactive plasticizers may be about 10%, yet the

maximum amount used in the formulation for plasticization may be only 5% by weight, again giving rise to a system than shrinks approximately 0.5%.

Even in the case where 50-100% reactive plasticizers are present, low shrinkage may be realized because the system is not now limited to non-viscous, flowable components. In the prior art, material systems were limited by low-viscosity requirements, which inherently translates to systems possessing a high population of reactive entities and therefore exhibiting large shrinkage upon cure. Because low viscosity is no longer a requirement with the practice of the present invention, semi-solid material systems with high viscosity, optionally high molecular weight, and inherently low shrinkage may now be utilized.

The molding compositions of the invention thus display low shrinkage upon cure. By "low shrinkage" is meant that the shrinkage of the composition of the invention upon cure will typically be less than about 5%, preferably less than about 2%. This benefit enables molding processes in which the fabricated part shows high replication fidelity of the mold cavity. That is, because shrinkage of the polymerizable formulation is quite small (typically less than 5%, more preferably less than 2%), the cured part will retain the shape of the mold cavity throughout cure. Problems associated with shrinkage such as premature mold release, which greatly hinder and complicate current state-of-the-art practices, are eliminated. Note that the present invention can also be practiced with other types of polymerizable systems, such as those initiated with ionic initiators, microwaves, x-rays, e-beams, or gamma radiation. In addition, condensation, ring-opening and other polymerization mechanisms may be similarly practiced.

The high replication fidelity achieved with the invention disclosed herewith may be appreciated in the casting of optical components which rely on precise, smooth surfaces such as ophthalmic lenses, contact lenses, prisms, optical disks and the like. High fidelity replication may be also appreciated in the molding of components that rely on surfaces having desired exact topographies, such as optical storage disks, printing plates or other pattern transfer media. High replication fidelity may be further appreciated in the molding of three dimensional or complex geometry components which require dimensionally precise replication from the mold such as couplers, housings, gears, various packaging assemblies, and the like.

It should be appreciated that the cross-linked interpenetrating polymer networks formed during the practice of the invention disclosed herewith provide continued dimensional precision during the use or operation of the molded part (i.e., dimensional stability). That is, the cross-linked networks do not flow when heated above their glass transition temperature, and provide improved resistance to chemical attack, repeated load cycles, and the like. The benefits of dimensional stability achieved with the practice of the invention will be appreciated by fabricators of all types of moldable objects which may benefit from precise geometries.

Another beneficial characteristic of the present invention is that free radical polymerization and other triggerable chain polymerization mechanisms (e.g., via the use of ionic initiators) proceed efficiently in semi-solid media because of reduced oxygen inhibition and slow termination reactions. Without being bound by theory, this is believed to be due in part to the decreased mobility of oxygen molecules in high-viscosity media. In addition, oxygen-scavenging additives may be incorporated into the polymerizable mixture prior to initiation of cure. Thus, semi-solid polymerizable mixtures allow processing in which the need for nitrogen purging during mixing and molding steps is reduced. Curing reactions will also proceed further to completion in the near-surface region of the object even when oxygen is present in the gas phase surrounding the object to be cured, thus reducing or eliminating the need for oxygen barrier layers at the surface of the molded part. UV initiators may further be chosen and incorporated in such concentrations so as to give rapid curing using UV-triggered polymerizations. By "rapid curing" is meant that the molded object may be substantially cured by UV light within about 1 hour, or as fast as a few minutes. Such curing regimens provide significantly faster curing cycles than the 8- to 24-hour curing cycle times typical in the current art.

Yet another beneficial characteristic of the disclosed invention is that thermal spikes produced by the polymerization of unsaturated species are mitigated. Conventional casting processes utilize low-viscosity systems, which contain near 100% reactive components. Such systems experience temperature spikes due to the exothermic curing reaction. When the entire part is irradiated and cured at once, part temperatures can increase rapidly by up to 200 °C over the part temperature prior to cure initiation due to the curing exotherm. Such temperature excursions lead to thermal degradation, discoloration, and part warpage upon being released from the mold due to thermal expansion-contraction effects.

The semi-solid-like nature of the polymerization mixture of this invention disclosed here greatly reduces such temperature spikes because the proportion of reactive components in the system is typically less than 50% by weight, and preferably less than 25% by weight, thereby substantially reducing the exotherm during cure. Thus, a mixture with only 25% by weight of the reactive plasticizer component will rise at most approximately 50 °C. Such temperature rises are easily withstood by most material formulations, and further, such a small temperature excursion precludes part warpage after mold release. Even when the amount of reactive plasticizer is above 50%, the semi-solid compositions will typically possess a low population of reactive entities, thus mitigating high temperature excursions and associated problems. Reduced exotherms will be appreciated by fabricators of precise, moldable objects, especially when parts containing thermally-sensitive constituents, or those having thick cross sections are to be fabricated.

This process enjoys the benefits of (1) material formulation flexibility, (2) finished parts being thermosets with interpenetrating networks or slightly crosslinked networks, (3) room temperature or slightly elevated temperature processing, (4) UV curing (photo-polymerization) that is not limited by heat transfer time or long cycle time, (5) rapid, efficient, low-oxygen-inhibited polymerization carried out in semi-solid media, (6) minimal temperature rise due to exothermic reactions, (7) low pressure operation, and (8) either continuous process or batch-wise operation with an intermediate step of casting from pre-forms (e.g., disks, slabs, balls, or pucks).

Two example process schemes are discussed below. Numerous variants can be envisioned by those skilled in the art of polymerization reaction engineering and polymer processing and molding. Hence, the present invention is not limited by these two example processing embodiments.

Batchwise processing provides precision-casting from pre-forms. A dead polymer, a reactive plasticizer, and an initiator package (optionally including other additives such as anti-oxidants, stabilizers, and the like) are mixed together (optionally with a waiting period during which the ingredients are not mechanically agitated) in a mixer equipped with temperature control and vacuum capabilities, to form a semi-solid polymerizable composition free of voids or air bubbles. The semi-solid composition is discharged from the mixer, and the discharge is cast into slabs (disks, pucks, balls, buttons, sheets, and the like), which serve as pre-forms for the subsequent precision casting operation. Alternatively, an extruded strand of the semi-solid composition can be sliced or diced into pre-forms. In a downstream operation, the pre-forms (which may be stored at room temperature or refrigerated temperatures in the interim, or which may even be partially cured to facilitate handling and storage) can be retrieved and shaped into the desired geometry for production of the final article. In a presently preferred embodiment, the pre-forms are placed in about the center of and sandwiched between two mold halves, whereupon the mold is closed, briefly heated to enhance material compliance as necessary, and flood-exposed by UV- or heat-cured. One can envision this processing scheme to suit just-in-time production situations, where an inventory of pre-forms can be used to make precise parts upon demand. In situations where a large variety of parts must be made just-in-time, this approach offers great ease of material handling. Eye glass lenses or contact lenses having a large range of prescriptions constitute one such example where this batchwise process scheme is appropriate.

In an alternative, continuous process, the dead polymer, the reactive plasticizer, and the initiator package (optionally including other additives such as anti-oxidants, stabilizers, and the like) are mixed together in an extruder. There is optionally a waiting period prior to the material being introduced into the extruder, during which time the ingredients are in intimate contact with one another, but are not mechanically agitated. Periodically, the extruder discharges a fixed amount of

semi-solid reactive plasticizer-dead polymer composition as a warm glob into approximately the center of a temperature-controlled mold cavity (or in such other manner that voids, bubbles, weld lines, and the like are minimized during the molding process). The mold, which exhibits a telescopic fit of the front/back mold assembly, is then closed. An optional waiting period may  
 5  
 10  
 15  
 20  
 25  
 30  
 35  
 40  
 45  
 50  
 55  
 60  
 65  
 70  
 75  
 80  
 85  
 90  
 95  
 100  
 105  
 110  
 115  
 120  
 125  
 130  
 135  
 140  
 145  
 150  
 155  
 160  
 165  
 170  
 175  
 180  
 185  
 190  
 195  
 200  
 205  
 210  
 215  
 220  
 225  
 230  
 235  
 240  
 245  
 250  
 255  
 260  
 265  
 270  
 275  
 280  
 285  
 290  
 295  
 300  
 305  
 310  
 315  
 320  
 325  
 330  
 335  
 340  
 345  
 350  
 355  
 360  
 365  
 370  
 375  
 380  
 385  
 390  
 395  
 400  
 405  
 410  
 415  
 420  
 425  
 430  
 435  
 440  
 445  
 450  
 455  
 460  
 465  
 470  
 475  
 480  
 485  
 490  
 495  
 500  
 505  
 510  
 515  
 520  
 525  
 530  
 535  
 540  
 545  
 550  
 555  
 560  
 565  
 570  
 575  
 580  
 585  
 590  
 595  
 600  
 605  
 610  
 615  
 620  
 625  
 630  
 635  
 640  
 645  
 650  
 655  
 660  
 665  
 670  
 675  
 680  
 685  
 690  
 695  
 700  
 705  
 710  
 715  
 720  
 725  
 730  
 735  
 740  
 745  
 750  
 755  
 760  
 765  
 770  
 775  
 780  
 785  
 790  
 795  
 800  
 805  
 810  
 815  
 820  
 825  
 830  
 835  
 840  
 845  
 850  
 855  
 860  
 865  
 870  
 875  
 880  
 885  
 890  
 895  
 900  
 905  
 910  
 915  
 920  
 925  
 930  
 935  
 940  
 945  
 950  
 955  
 960  
 965  
 970  
 975  
 980  
 985  
 990  
 995  
 1000  
 1005  
 1010  
 1015  
 1020  
 1025  
 1030  
 1035  
 1040  
 1045  
 1050  
 1055  
 1060  
 1065  
 1070  
 1075  
 1080  
 1085  
 1090  
 1095  
 1100  
 1105  
 1110  
 1115  
 1120  
 1125  
 1130  
 1135  
 1140  
 1145  
 1150  
 1155  
 1160  
 1165  
 1170  
 1175  
 1180  
 1185  
 1190  
 1195  
 1200  
 1205  
 1210  
 1215  
 1220  
 1225  
 1230  
 1235  
 1240  
 1245  
 1250  
 1255  
 1260  
 1265  
 1270  
 1275  
 1280  
 1285  
 1290  
 1295  
 1300  
 1305  
 1310  
 1315  
 1320  
 1325  
 1330  
 1335  
 1340  
 1345  
 1350  
 1355  
 1360  
 1365  
 1370  
 1375  
 1380  
 1385  
 1390  
 1395  
 1400  
 1405  
 1410  
 1415  
 1420  
 1425  
 1430  
 1435  
 1440  
 1445  
 1450  
 1455  
 1460  
 1465  
 1470  
 1475  
 1480  
 1485  
 1490  
 1495  
 1500  
 1505  
 1510  
 1515  
 1520  
 1525  
 1530  
 1535  
 1540  
 1545  
 1550  
 1555  
 1560  
 1565  
 1570  
 1575  
 1580  
 1585  
 1590  
 1595  
 1600  
 1605  
 1610  
 1615  
 1620  
 1625  
 1630  
 1635  
 1640  
 1645  
 1650  
 1655  
 1660  
 1665  
 1670  
 1675  
 1680  
 1685  
 1690  
 1695  
 1700  
 1705  
 1710  
 1715  
 1720  
 1725  
 1730  
 1735  
 1740  
 1745  
 1750  
 1755  
 1760  
 1765  
 1770  
 1775  
 1780  
 1785  
 1790  
 1795  
 1800  
 1805  
 1810  
 1815  
 1820  
 1825  
 1830  
 1835  
 1840  
 1845  
 1850  
 1855  
 1860  
 1865  
 1870  
 1875  
 1880  
 1885  
 1890  
 1895  
 1900  
 1905  
 1910  
 1915  
 1920  
 1925  
 1930  
 1935  
 1940  
 1945  
 1950  
 1955  
 1960  
 1965  
 1970  
 1975  
 1980  
 1985  
 1990  
 1995  
 2000  
 2005  
 2010  
 2015  
 2020  
 2025  
 2030  
 2035  
 2040  
 2045  
 2050  
 2055  
 2060  
 2065  
 2070  
 2075  
 2080  
 2085  
 2090  
 2095  
 2100  
 2105  
 2110  
 2115  
 2120  
 2125  
 2130  
 2135  
 2140  
 2145  
 2150  
 2155  
 2160  
 2165  
 2170  
 2175  
 2180  
 2185  
 2190  
 2195  
 2200  
 2205  
 2210  
 2215  
 2220  
 2225  
 2230  
 2235  
 2240  
 2245  
 2250  
 2255  
 2260  
 2265  
 2270  
 2275  
 2280  
 2285  
 2290  
 2295  
 2300  
 2305  
 2310  
 2315  
 2320  
 2325  
 2330  
 2335  
 2340  
 2345  
 2350  
 2355  
 2360  
 2365  
 2370  
 2375  
 2380  
 2385  
 2390  
 2395  
 2400  
 2405  
 2410  
 2415  
 2420  
 2425  
 2430  
 2435  
 2440  
 2445  
 2450  
 2455  
 2460  
 2465  
 2470  
 2475  
 2480  
 2485  
 2490  
 2495  
 2500  
 2505  
 2510  
 2515  
 2520  
 2525  
 2530  
 2535  
 2540  
 2545  
 2550  
 2555  
 2560  
 2565  
 2570  
 2575  
 2580  
 2585  
 2590  
 2595  
 2600  
 2605  
 2610  
 2615  
 2620  
 2625  
 2630  
 2635  
 2640  
 2645  
 2650  
 2655  
 2660  
 2665  
 2670  
 2675  
 2680  
 2685  
 2690  
 2695  
 2700  
 2705  
 2710  
 2715  
 2720  
 2725  
 2730  
 2735  
 2740  
 2745  
 2750  
 2755  
 2760  
 2765  
 2770  
 2775  
 2780  
 2785  
 2790  
 2795  
 2800  
 2805  
 2810  
 2815  
 2820  
 2825  
 2830  
 2835  
 2840  
 2845  
 2850  
 2855  
 2860  
 2865  
 2870  
 2875  
 2880  
 2885  
 2890  
 2895  
 2900  
 2905  
 2910  
 2915  
 2920  
 2925  
 2930  
 2935  
 2940  
 2945  
 2950  
 2955  
 2960  
 2965  
 2970  
 2975  
 2980  
 2985  
 2990  
 2995  
 3000  
 3005  
 3010  
 3015  
 3020  
 3025  
 3030  
 3035  
 3040  
 3045  
 3050  
 3055  
 3060  
 3065  
 3070  
 3075  
 3080  
 3085  
 3090  
 3095  
 3100  
 3105  
 3110  
 3115  
 3120  
 3125  
 3130  
 3135  
 3140  
 3145  
 3150  
 3155  
 3160  
 3165  
 3170  
 3175  
 3180  
 3185  
 3190  
 3195  
 3200  
 3205  
 3210  
 3215  
 3220  
 3225  
 3230  
 3235  
 3240  
 3245  
 3250  
 3255  
 3260  
 3265  
 3270  
 3275  
 3280  
 3285  
 3290  
 3295  
 3300  
 3305  
 3310  
 3315  
 3320  
 3325  
 3330  
 3335  
 3340  
 3345  
 3350  
 3355  
 3360  
 3365  
 3370  
 3375  
 3380  
 3385  
 3390  
 3395  
 3400  
 3405  
 3410  
 3415  
 3420  
 3425  
 3430  
 3435  
 3440  
 3445  
 3450  
 3455  
 3460  
 3465  
 3470  
 3475  
 3480  
 3485  
 3490  
 3495  
 3500  
 3505  
 3510  
 3515  
 3520  
 3525  
 3530  
 3535  
 3540  
 3545  
 3550  
 3555  
 3560  
 3565  
 3570  
 3575  
 3580  
 3585  
 3590  
 3595  
 3600  
 3605  
 3610  
 3615  
 3620  
 3625  
 3630  
 3635  
 3640  
 3645  
 3650  
 3655  
 3660  
 3665  
 3670  
 3675  
 3680  
 3685  
 3690  
 3695  
 3700  
 3705  
 3710  
 3715  
 3720  
 3725  
 3730  
 3735  
 3740  
 3745  
 3750  
 3755  
 3760  
 3765  
 3770  
 3775  
 3780  
 3785  
 3790  
 3795  
 3800  
 3805  
 3810  
 3815  
 3820  
 3825  
 3830  
 3835  
 3840  
 3845  
 3850  
 3855  
 3860  
 3865  
 3870  
 3875  
 3880  
 3885  
 3890  
 3895  
 3900  
 3905  
 3910  
 3915  
 3920  
 3925  
 3930  
 3935  
 3940  
 3945  
 3950  
 3955  
 3960  
 3965  
 3970  
 3975  
 3980  
 3985  
 3990  
 3995  
 4000  
 4005  
 4010  
 4015  
 4020  
 4025  
 4030  
 4035  
 4040  
 4045  
 4050  
 4055  
 4060  
 4065  
 4070  
 4075  
 4080  
 4085  
 4090  
 4095  
 4100  
 4105  
 4110  
 4115  
 4120  
 4125  
 4130  
 4135  
 4140  
 4145  
 4150  
 4155  
 4160  
 4165  
 4170  
 4175  
 4180  
 4185  
 4190  
 4195  
 4200  
 4205  
 4210  
 4215  
 4220  
 4225  
 4230  
 4235  
 4240  
 4245  
 4250  
 4255  
 4260  
 4265  
 4270  
 4275  
 4280  
 4285  
 4290  
 4295  
 4300  
 4305  
 4310  
 4315  
 4320  
 4325  
 4330  
 4335  
 4340  
 4345  
 4350  
 4355  
 4360  
 4365  
 4370  
 4375  
 4380  
 4385  
 4390  
 4395  
 4400  
 4405  
 4410  
 4415  
 4420  
 4425  
 4430  
 4435  
 4440  
 4445  
 4450  
 4455  
 4460  
 4465  
 4470  
 4475  
 4480  
 4485  
 4490  
 4495  
 4500  
 4505  
 4510  
 4515  
 4520  
 4525  
 4530  
 4535  
 4540  
 4545  
 4550  
 4555  
 4560  
 4565  
 4570  
 4575  
 4580  
 4585  
 4590  
 4595  
 4600  
 4605  
 4610  
 4615  
 4620  
 4625  
 4630  
 4635  
 4640  
 4645  
 4650  
 4655  
 4660  
 4665  
 4670  
 4675  
 4680  
 4685  
 4690  
 4695  
 4700  
 4705  
 4710  
 4715  
 4720  
 4725  
 4730  
 4735  
 4740  
 4745  
 4750  
 4755  
 4760  
 4765  
 4770  
 4775  
 4780  
 4785  
 4790  
 4795  
 4800  
 4805  
 4810  
 4815  
 4820  
 4825  
 4830  
 4835  
 4840  
 4845  
 4850  
 4855  
 4860  
 4865  
 4870  
 4875  
 4880  
 4885  
 4890  
 4895  
 4900  
 4905  
 4910  
 4915  
 4920  
 4925  
 4930  
 4935  
 4940  
 4945  
 4950  
 4955  
 4960  
 4965  
 4970  
 4975  
 4980  
 4985  
 4990  
 4995  
 5000  
 5005  
 5010  
 5015  
 5020  
 5025  
 5030  
 5035  
 5040  
 5045  
 5050  
 5055  
 5060  
 5065  
 5070  
 5075  
 5080  
 5085  
 5090  
 5095  
 5100  
 5105  
 5110  
 5115  
 5120  
 5125  
 5130  
 5135  
 5140  
 5145  
 5150  
 5155  
 5160  
 5165  
 5170  
 5175  
 5180  
 5185  
 5190  
 5195  
 5200  
 5205  
 5210  
 5215  
 5220  
 5225  
 5230  
 5235  
 5240  
 5245  
 5250  
 5255  
 5260  
 5265  
 5270  
 5275  
 5280  
 5285  
 5290  
 5295  
 5300  
 5305  
 5310  
 5315  
 5320  
 5325  
 5330  
 5335  
 5340  
 5345  
 5350  
 5355  
 5360  
 5365  
 5370  
 5375  
 5380  
 5385  
 5390  
 5395  
 5400  
 5405  
 5410  
 5415  
 5420  
 5425  
 5430  
 5435  
 5440  
 5445  
 5450  
 5455  
 5460  
 5465  
 5470  
 5475  
 5480  
 5485  
 5490  
 5495  
 5500  
 5505  
 5510  
 5515  
 5520  
 5525  
 5530  
 5535  
 5540  
 5545  
 5550  
 5555  
 5560  
 5565  
 5570  
 5575  
 5580  
 5585  
 5590  
 5595  
 5600  
 5605  
 5610  
 5615  
 5620  
 5625  
 5630  
 5635  
 5640  
 5645  
 5650  
 5655  
 5660  
 5665  
 5670  
 5675  
 5680  
 5685  
 5690  
 5695  
 5700  
 5705  
 5710  
 5715  
 5720  
 5725  
 5730  
 5735  
 5740  
 5745  
 5750  
 5755  
 5760  
 5765  
 5770  
 5775  
 5780  
 5785  
 5790  
 5795  
 5800  
 5805  
 5810  
 5815  
 5820  
 5825  
 5830  
 5835  
 5840  
 5845  
 5850  
 5855  
 5860  
 5865  
 5870  
 5875  
 5880  
 5885  
 5890  
 5895  
 5900  
 5905  
 5910  
 5915  
 5920  
 5925  
 5930  
 5935  
 5940  
 5945  
 5950  
 5955  
 5960  
 5965  
 5970  
 5975  
 5980  
 5985  
 5990  
 5995  
 6000  
 6005  
 6010  
 6015  
 6020  
 6025  
 6030  
 6035  
 6040  
 6045  
 6050  
 6055  
 6060  
 6065  
 6070  
 6075  
 6080  
 6085  
 6090  
 6095  
 6100  
 6105  
 6110  
 6115  
 6120  
 6125  
 6130  
 6135  
 6140  
 6145  
 6150  
 6155  
 6160  
 6165  
 6170  
 6175  
 6180  
 6185  
 6190  
 6195  
 6200  
 6205  
 6210  
 6215  
 6220  
 6225  
 6230  
 6235  
 6240  
 6245  
 6250  
 6255  
 6260  
 6265  
 6270  
 6275  
 6280  
 6285  
 6290  
 6295  
 6300  
 6305  
 6310  
 6315  
 6320  
 6325  
 6330  
 6335  
 6340  
 6345  
 6350  
 6355  
 6360  
 6365  
 6370  
 6375  
 6380  
 6385  
 6390  
 6395  
 6400  
 6405  
 6410  
 6415  
 6420  
 6425  
 6430  
 6435  
 6440  
 6445  
 6450  
 6455  
 6460  
 6465  
 6470  
 6475  
 6480  
 6485  
 6490  
 6495  
 6500  
 6505  
 6510  
 6515  
 6520  
 6525  
 6530  
 6535  
 6540  
 6545  
 6550  
 6555  
 6560  
 6565  
 6570  
 6575  
 6580  
 6585  
 6590  
 6595  
 6600  
 6605  
 6610  
 6615  
 6620  
 6625  
 6630  
 6635  
 6640  
 6645  
 6650  
 6655  
 6660  
 6665  
 6670  
 6675  
 6680  
 6685  
 6690  
 6695  
 6700  
 6705  
 6710  
 6715  
 6720  
 6725  
 6730  
 6735  
 6740  
 6745  
 6750  
 6755  
 6760  
 6765  
 6770  
 6775  
 6780  
 6785  
 6790  
 6795  
 6800  
 6805  
 6810  
 6815  
 6820  
 6825  
 6830  
 6835  
 6840  
 6845  
 6850  
 6855  
 6860  
 6865  
 6870  
 6875  
 6880  
 6885  
 6890  
 6895  
 6900  
 6905  
 6910  
 6915  
 6920  
 69

replication of the mold cavity. Precise geometric replication of the mold cavity is further preserved due to the relatively low molding temperatures and reduced exotherm from polymerization, which is particularly applicable to part designs having thick cross-sections.

Subsequent discussions concerning the basic material design considerations are divided into two categories based on the type of dead polymer utilized in the process. One category begins with standard thermoplastics as the dead polymer. These include, but are not limited to, polystyrene, polymethylmethacrylate, poly(acrylonitrile-butadiene-styrene), polyvinyl chloride, polycarbonate, polysulfone, polyvinylpyrrolidone, polycaprolactone, and polyetherimide, for example. The thermoplastics may optionally have small amounts of reactive entities attached (copolymerized, grafted, or otherwise incorporated) to the polymer backbone to promote crosslinking upon cure. They may be amorphous or crystalline. They may be classified as high performance engineering thermoplastics (e.g., polyether imides, polysulfones, polyether ketones, etc.), or they may be biodegradable (starch, prolamine, and cellulose, for example). These examples are not meant to limit the scope of compositions possible during the practice of the current invention, but merely to illustrate the broad selection of thermoplastic chemistries permitted under the present disclosure. Reactive plasticizers may be mixed with a thermoplastic polymer such as those listed above to give a semi-solid-like composition that can be easily molded into dimensionally precise objects. Upon polymerizing to form a cured resin, the dimensional stability of the object is locked in to give exact three-dimensional shapes or precise surface features.

Thermoplastic polymers may be chosen in order to give optical clarity, high index of refraction, low birefringence, exceptional impact resistance, good thermal stability, high oxygen permeability, UV transparency or blocking, low cost, or a combination of these properties in the finished, molded object.

The other category utilizes "thermoplastic elastomers" as the dead polymer. An exemplary thermoplastic elastomer is a tri-block copolymer of the general structure "A-B-A", where A is a thermoplastic rigid polymer (i.e., having a glass transition temperature above ambient) and B is an elastomeric (rubbery) polymer (glass transition temperature below ambient). In the pure state, ABA forms a microphase-separated morphology. This morphology consists of rigid glassy polymer regions (A) connected and surrounded by rubbery chains (B), or occlusions of the rubbery phase (B) surrounded by a glassy (A) continuous phase, depending on the relative amounts of (A) and (B) in the polymer. Under certain compositional and processing conditions, the morphology is such that the relevant domain size is smaller than the wavelength of visible light. Hence, parts made of such ABA copolymers can be transparent or at worst translucent. Thermoplastic elastomers, without vulcanization, have rubber-like properties similar to those of conventional rubber vulcanizates, but flow as thermoplastics at temperatures above the glass transition point of the

glassy polymer region. Melt behavior with respect to shear and elongation is similar to that of conventional thermoplastics. Commercially important thermoplastic elastomers are exemplified by SBS, SIS, and SEBS, where S is polystyrene and B is polybutadiene, I is polyisoprene, and EB is ethylenebutylene copolymer. Many other di-block or tri-block candidates are known, such as poly(aromatic amide)-siloxane, polyimide-siloxane, and polyurethanes. SBS and hydrogenated SBS (i.e., SEBS) are well-known products from Shell Chemicals (Kraton®). DuPont's Lycra® is also a block copolymer.

When thermoplastic elastomers are chosen as the starting dead polymer for formulation, exceptionally impact-resistant parts may be manufactured by mixing with reactive plasticizers. The thermoplastic elastomers, by themselves, are not chemically crosslinked and require relatively high-temperature processing steps for molding which, upon cooling, leads to dimensionally unstable, shrunken or warped parts. The reactive plasticizers, if cured by themselves, may be chosen to form a relatively glassy, rigid network, or may be chosen to form a relatively soft, rubbery network, but with relatively high shrinkage. When thermoplastic elastomers and reactive plasticizers are blended together and reacted to form a cured resin, they form flexible networks with superior shock-absorbing and impact-resistant properties. By "impact-resistant" is meant resistance to fracture or shattering upon being struck by an incident object. Depending on the nature of the dead polymer and reactive plasticizers used in the formulation, the final cured resin may be more stiff or more stretchy than the starting dead polymer. Composite articles exhibiting exceptional toughness may be fabricated by using a thermoplastic elastomer which itself contains polymerizable groups along the polymer chain, such as SBS tri-block copolymers, for example.

Furthermore, when compatible systems are identified, transparent objects can be cast. "Compatibility" refers to the thermodynamic state where the dead polymer is solvated by the reactive plasticizers. Hence, molecular segments with structural similarity would promote mutual dissolution. Aromatic moieties on the polymer generally dissolve in aromatic plasticizers, and vice versa. Hydrophilicity and hydrophobicity are additional considerations in choosing the reactive plasticizers to mix with a given dead polymer. Even when only partial compatibility is observed at room temperature, the mixture often becomes uniform at a slightly increased temperature; i.e., many systems become clear at slightly elevated temperatures. Such temperatures may be slightly above ambient temperatures or may extend up to the vicinity of 100 °C. In such cases, the reactive components can be quickly cured at the elevated temperature to "lock-in" the compatible morphology in the cured resin before system cool-down. Hence, both material and processing approaches can be exploited to produce optically clear parts. Optically clear and dimensionally exact parts have a wide range of potential applications. For example, optically clear materials such as polycarbonate, polystyrene, polymethyl methacrylate, polysulfone, polyphenylene oxide,



polyethylene terephthalate, polyolefins, thermoplastic elastomers, polyurethanes, and variations, copolymers, and/or mixtures thereof can be employed to create useful formulations by mixing with suitable reactive plasticizer packages. Optically transparent phase-separated systems may be beneficial prepared by combining a phase-separated iso-refractive mixture as the dead polymers in the system. When a reactive plasticizer is added which either (1) partitions itself approximately equally between the phases or (2) has a refractive index upon polymerizing similar to that of the dead polymer mixture, a clear part results upon curing. Alternatively, when the reactive plasticizer does not partition itself equally between the phases and does not possess a refractive index upon curing similar to the polymer mixture, the refractive index of one of the phases may be altered to give a resultant iso-refractive mixture. With the process innovation described herewith, powerful new material systems can be developed.

A preferred formulation for developing optically clear and high impact-resistant materials uses cyclo-olefin polymers and/or cyclo-olefin copolymers (polyolefins) such as the cyclo-olefin Zeonor from Zeon Chemicals as a dead polymer. Formulations based on one or more of the Zeonor grades (1020R, 1060R, 1420R, 1600, etc.) exhibit excellent optical properties, impact resistance, thermal stability, good hardness, low water absorption, and low density (approximately 1.01 g/cc for the pure polymer).

Another preferred formulation for developing optically clear and high impact-resistant materials uses styrene-rich SBS tri-block copolymers that contain up to about 75 % styrene. These SBS copolymers are commercially available from Shell Chemicals (Kraton®), Phillips Chemical Company (K-Resin®), BASF (Styrolux®), Fina Chemicals (Finaclear®), and Asahi Chemical (Asaflex®). In addition to high impact resistance and good optical clarity, such styrene-rich copolymers yield materials systems which preferably exhibit other desirable properties such as a relatively high refractive index (that is, the index of refraction is equal to or greater than about 1.54) and low density (their densities are less than about 1.2 g/cc, and more typically are about 1.0 g/cc).

When the mixture refractive index is an especially important consideration, high refractive index polymers may be used as one or more of the dead-polymer components. Examples of such polymers include polycarbonates and halogenated polycarbonates, polystyrenes and halogenated polystyrenes, polystyrene-polybutadiene block copolymers and their hydrogenated and halogenated versions (all of which may be linear, branched, star-shaped, or non-symmetrically branched or star-shaped), polystyrene-polyisoprene block copolymers and their hydrodogenated and halogenated versions (including the linear, branched, star-shaped, and non-symmetrical branched and star-shaped variations), poly(pentabromophenyl (meth)acrylate), polyvinyl carbazole, polyvinyl naphthalene, poly vinyl biphenyl, polynaphthyl (meth)acrylate, polyvinyl thiophene, polysulfones, polyphenylene sulfides, urea-, phenol-, or naphthyl-formaldehyde resins,

polyvinyl phenol, chlorinated or brominated polystyrenes, poly(phenyl  $\alpha$ - or  $\beta$ -bromoacrylate), polyvinylidene chloride or bromide, and the like. In general, increasing the aromatic content and the halogen content (especially bromine) are effective means well-known in the art for increasing the refractive index of a material. These properties are especially preferred for ophthalmic lenses as it enables the production of ultra thin, light-weight eyeglass lenses which are desirable for low-profile appearances and comfort of the wearer.

Alternatively, elastomers, thermosets (e.g., epoxies, melamines, acrylated epoxies, acrylated urethanes, etc., in their uncured state), and other non-thermoplastic polymeric compositions may be desirably utilized during the practice of this invention.

Mixtures of such materials may also be beneficially used to create dimensionally stable parts with desirable properties. For example, impact modifiers may be blended into various thermoplastics or thermoplastic elastomers to improve the impact strength of the final cured resin. In such cases, the presence of the reactive plasticizers will facilitate blending by lowering the softening temperature of the polymers to be blended. This is especially beneficial when a temperature-sensitive material is being blended with a high- $T_g$  polymer. When optically clear materials are desired, the mixture components may be chosen to have the same refractive index (iso-refractive) such that light scattering is reduced. When iso-refractive components are not available, the reactive plasticizers may also help reduce the domain size between two immiscible polymers to below the wavelength of light, thus producing an optically clear polymer mixture which would have otherwise been opaque.

The reactive diluents (plasticizers) can be used singly or, alternatively, mixtures can be used to facilitate dissolution of a given dead polymer. The reactive functional group can be acrylate, methacrylate, acrylic anhydride, acrylamide, vinyl, vinyl ether, vinyl ester, vinyl halide, vinyl silane, vinyl siloxane, (meth)acrylated silicones, vinyl heterocycles, diene, allyl and the like.

Other less known but polymerizable functional groups can be investigated, such as epoxies (with hardeners) and urethanes (reaction between isocyanates and alcohols). In principle, any monomers may be used as reactive plasticizers in accordance with the present invention, although preference is given to those which exist as liquids at ambient temperatures or slightly above, and which polymerize readily with the application of a source of polymerizing energy such as light or heat in the presence of a suitable initiator.

Reactive monomers, oligomers, and crosslinkers that contain acrylate or methacrylate functional groups are well known and commercially available from Sartomer, Radcure and Henkel. Similarly, vinyl ethers are commercially available from Allied Signal. Radcure also supplies UV curable cycloaliphatic epoxy resins. Photo-initiators such as the Irgacure and Darocur series are well-known and commercially available from Ciba Geigy, as is the Esacure series from Sartomer.

Thermal initiators such as azobisisobutyronitrile (AIBN), benzoyl peroxide, dicumyl peroxide, t-butyl hydroperoxide, and potassium persulfate are also well known and are available from chemical suppliers such as Aldrich. Vinyl, diene, and allyl compounds are available from a large number of chemical suppliers, as is benzophenone. For a reference on initiators, see, for example, Polymer Handbook, J. Brandrup, E.H. Immergut, eds., 3<sup>rd</sup> Ed., Wiley, New York, 1989. Below we will use acrylates (and in a few cases, methacrylates) to illustrate the flexibility of our formulation approach. Similar structures with other reactive groups based on either small or large molecule architectures (such as acrylamides, vinyl ethers, vinyls, dienes, and the like) can be used in conjunction with the disclosed casting process.

The compatibility of dead polymer-reactive plasticizer mixtures is demonstrated by checking the optical transparency of the resulting material at room temperature or slightly above, as illustrated by Example 1 below. To demonstrate the great diversity of reactive plasticizers that can be used to achieve such compatibility, we will name only a few from a list of hundreds to thousands of commercially available compounds. For example, mono-functional entities include, but are not limited to: isodecyl acrylate, hexadecyl acrylate, stearyl acrylate, isobornyl acrylate, vinyl benzoate, tetrahydrofurfuryl acrylate (or methacrylate), caprolactone acrylate, cyclohexyl acrylate, methyl methacrylate, ethyl acrylate, propyl acrylate, and butyl acrylate, etc. Bi-functional entities include, but are not limited to: polyethyleneglycol diacrylate, polypropyleneglycol diacrylate, hexanediol diacrylate, Photomer 4200 (from Henkel), polybutadiene diacrylate (or dimethacrylate), Ebecryl 8402 (from Radcure), bisphenol A diacrylate, ethoxylated (or propoxylated) bisphenol A diacrylate. Tri-functional and multi-functional entities include, but are not limited to: trimethylolpropane triacrylate (and its ethoxylated or propoxylated derivatives), pentaerythritol tetraacrylate (and its ethoxylated or propoxylated derivatives), Photomer 6173 (a proprietary acrylated oligomer of multi functionality, from Henkel), and a whole host of aliphatic and aromatic acrylated oligomers from Sartomer (the SR series), Radcure (the Ebecryl series), and Henkel (the Photomer series).

When high refractive index materials are desired, the reactive plasticizers may be chosen accordingly to have high refractive indices. Examples of such reactive plasticizers, in addition to those mentioned above, include brominated or chlorinated phenyl (meth)acrylates (e.g., pentabromo methacrylate, tribromo acrylate, etc.), brominated or chlorinated naphthyl or biphenyl (meth)acrylates, brominated or chlorinated styrenes, tribromoneopentyl (meth)acrylate, vinyl naphthylene, vinyl biphenyl, vinyl phenol, vinyl carbazole, vinyl bromide or chloride, vinylidene bromide or chloride, bromoethyl (meth)acrylate, bromophenyl isocyanate, and the like.

EXAMPLES:

The following examples are provided to illustrate the practice of the present invention, and are intended neither to define nor to limit the scope of the invention in any manner.

5       The Examples 1 to 8 below are designed to discover pairs of materials that exhibit thermodynamic compatibility prior to polymerization. Examples 9 to 11 show systems that remain optically clear upon photocuring, and further illustrate material systems exhibiting high refractive indices. Tertiary, quaternary, and multi-component mixtures can be formulated based on knowledge gleaned from binary experiments. Generally, diluents that are small molecules have a higher degree of shrinkage. But, they are also typically better plasticizers. On the contrary, oligomeric plasticizers shrink less, but they also show less solvation power and less viscosity reduction. Hence, mixtures of reactive plasticizers can be prepared to give optimized compatibility, processing, and shrinkage properties.

15       Example 1. Experimental Protocol

Dead polymers are added to a vial, pre-filled with a small quantity of the intended reactive plasticizer. Gentle heating is applied while stirring homogenizes the mixture. The resulting semi-solid-like mass is observed visually and optical transparency at various temperatures is recorded. Complete clarity is indicative of component miscibility. A faint haze suggests partial miscibility, and opacity equates to incompatibility (light scattering as a result of phase separation). Many pairs of dead polymer-reactive plasticizers can thus be investigated.

Examples 2 to 8 report several findings of system compatibility and partial compatibility, following this procedure.

25       Example 2. Kraton-Based Systems

The following polymers are studied using the protocol described in Example 1. The accompanying table summarizes the polymer characteristics.

TABLE 1

Kraton type	Composition (%)	Description
G 1652	SEBS (S:29 / EB:71)	linear, low molecular weight
G 1650	SEBS (S:29 / EB:71)	linear, medium Mw
G 1657	SEBS (S:13 / EB:87)	linear
D 1102	SBS (S:28 / B:72)	linear, low Mw
D 4141	SBS (S:31 / B:69)	linear
D 4240p	(SB) <sub>n</sub> (S:44 / B:56)	branched
D 1116	(SB) <sub>n</sub> (S:21 / B:79)	branched
D 1107	SIS (S:14 / I:86)	linear

S = styrene, EB = ethylene butylene, B = butadiene, I = isoprene

5 Hexanediol diacrylate solvates all Kraton samples well except for G 1650, which shows partial miscibility. Photomer 4200 solvates D1102, D1107, D4141, D4240p, and G1657 at elevated temperatures. Photomer 4200 (an oligomeric diacrylate) solvates G 1652 partially. Polybutadiene dimethacrylate (Sartomer CN301) solvates D1116, D1102, and D4141 partially at elevated temperatures. Ebecryl 8402 solvates G 1657. Isodecyl acrylate is compatible with all of the above Kratons. Hexadecyl acrylate, lauryl acrylate, and stearyl acrylate solvate Kraton at elevated temperatures.

10 Other monomers that solvate Kraton include butyl acrylate, isooctyl acrylate, isobornyl acrylate, benzyl acrylate, tetrahydrofurfuryl acrylate, and vinyl benzoate. In general, aliphatic acrylates solvate rubbery Kraton well. Ethoxylated bisphenol A diacrylate (average molecular weight of 424) solvates Kraton D4240p, D1107, D4141, and D1102 only slightly.

### 15 Example 3. Styrene-Rich-SBS Systems

Kraton D1401P is a linear styrene-rich SBS tri-block copolymer. Reactive plasticizers that solvate Kraton D1401P include: vinyl benzoate; tetrahydrofurfuryl acrylate; benzyl acrylate; isobornyl acrylate; butyl acrylate; octyl acrylate; isodecyl acrylate; butanediol diacrylate; hexanediol diacrylate; and ethoxylated bisphenol A diacrylate.

20 To obtain thermodynamically compatible systems containing styrene-rich SBS tri-block copolymers, Kraton D1401P can be replaced by other SBS copolymers such as those that are commercially available from Phillips Chemical Company (K-Resin), BASF (Styrolux), Fina Chemicals (Finaclear), and Asahi Chemical (Asaflex).

**Example 4. PMMA-Based Systems**

This study is conducted with a polymethyl methacrylate (PMMA) sample of molecular weight 25,000. Many reactive plasticizers have been found compatible with PMMA. These are: Photomer 4200; Photomer 6173; many alkoxyated multifunctional acrylate esters, such as propoxylated glycerol triacrylate; urethane acrylates, such as Ebecryl 8402 (aliphatic) and Ebecryl 4827, 4849 and 6700 (aromatic); tetrahydrofurfuryl acrylate; benzyl acrylate; butyl acrylate; butanediol diacrylate; hexanediol diacrylate; octyldecyl acrylate; isobornyl acrylate; and ethoxylated bisphenol A diacrylate.

**Example 5. Polystyrene-Based Systems**

Acrylated plasticizers that solvate polystyrene include Photomer 4200, tetrahydrofurfuryl acrylate, isodecyl acrylate. Bisphenol A diacrylate, hexadecyl acrylate, and stearyl acrylate exhibit compatibility at elevated temperatures (approximately 100 °C for example).

**Example 6. Polycarbonate-Based Systems**

Bisphenol A diacrylate, alkoxyated bisphenol A diacrylate, cycloaliphatic epoxy resin, N-vinyl-2-pyrrolidinone, and tetrahydrofurfuryl acrylate, among others, have been found useful for the solvation of polycarbonate at elevated temperature. Several aromatic urethane acrylates can be mixed with the above compounds to aid the compatibility of the ingredients.

**Example 7. ARTON-Based Systems**

Reactive plasticizers that solvate ARTON FX4727T1 (JSR Corporation) are: benzyl acrylate; isobornyl acrylate; isobornyl methacrylate; butyl acrylate; octyl acrylate; isooctyl acrylate; isodecyl acrylate; lauryl acrylate; behenyl acrylate. Aliphatic acrylates solvate ARTON very well.

**Example 8. ZEONEX-Based Systems**

Octyldecyl acrylate, butyl acrylate, and isooctyl acrylate solvate Zeonex 480R (Nippon Zeon Co., Ltd). Isobornyl acrylate solvates Zeonex 480R and E48R, and Zeonor 1420R, 1020R and 1600R. Lauryl acrylate and behenyl acrylate solvate ZEONEX 480R and E48R at elevated temperature.

**Example 9. Transparent Photo-cured Systems**

Mixtures containing the dead polymer, reactive plasticizer, and photoinitiator were mixed by the protocol described in Example 1. The amount of reactive plasticizer was typically 3% to 25%

and the photoinitiator was 1% to 5% by weight. Example photoinitiators include Esacure KT046 from Sartomer and Irgacure 184 from Ciba Geigy.

The resulting semi-solid composition was slightly heated (less than or equal to about 100 °C), pressed between flat glass plates, and flood-exposed by UV light. Rapid polymerization was observed that led to a clear and solid-like material.

The examples of transparent photo-cured systems included: Kraton D1401P-based systems reported by Example 3; PMMA-based systems reported by Example 4; ARTON-based systems reported by Example 7. Kraton D1401P-based systems also showed exceptional impact-resistance.

#### Example 10. Transparent Photo-cured Systems Having a High Refractive Index

A mixture containing a dead polymer, reactive plasticizer, and photoinitiator was mixed by the protocol described in Example 1, and was processed further as described in Example 9. The dead polymer was Kraton D1401P and the reactive plasticizer was benzyl acrylate, mixed at a ratio by weight of 88/12. Irgacure 184 was added to the mixture at 2 wt% based on the overall weight of the system. Upon UV cure, a flat sample having a thickness of 2.4 millimeters was produced, which showed 88% light transmittance at a wavelength of 700 nm. The refractive index of the cured sample was 1.578 at the sodium D line at room temperature.

#### Example 11. Transparent Systems Utilizing a Waiting Period

Kraton D1401P and isooctyl acrylate were added to a glass vial in the weight ratio 93/7. The capped vial was allowed to sit overnight. After 24 hours, the mixture was a clear, semi-solid mass. Irgacure 184 was added to the mixture at 2 wt% (based on the overall weight of the system), and was dissolved into the system while slightly heating and mixing manually. The resulting semi-solid mass was processed further as described in Example 9. Upon UV cure, a flat sample having a thickness of 2.3 millimeters was produced, which showed 90% light transmittance at a wavelength of 700 nm. The refractive index of the cured sample was 1.574 at the sodium D line at room temperature.